



## Core-Floorer High-Grade Floor Paint

Marketed by:  
**Amport International (HK) Limited**  
Tel : (852) 2341 2388 Fax : (852) 2341 8904 E-Mail : info@amport-group.com

### *Description*

*Core-Floorer – High Grade Floor Paint is a new high technology product which differs from the others. It has high adhesive strength, anti-compressive strength, anti-friction, anti-acidic, anti-alkaline and anti-thermal properties. It can be used in a high humidity environment and is ideal for floor painting.*

### *Product Property*

- *Short drying period*
- *No crack or peel off*
- *High adhesive strength*
- *Anti-compressive strength*
- *Anti-friction*
- *High anti-acidic, anti-alkaline and anti-chemical property*
- *Simple usage and Applying method*

### *Application*

- *Industrial plant flooring*
- *Car-park flooring*
- *Chemical plant flooring*
- *Pool base*
- *Machine base setting*

### *Applying Method*

1. *Remove all loose particles, dust, grease and other contaminants from substrate surface.*
2. *Mix the two ingredients in weight ratio  $A : B = 1 : 2$  by a simple stirrer and set for use within 60 minutes. Over which, the mixture will become solidified.*
3. *Apply mixture evenly onto substrate surface by brush, roller or spray, or by injection to repair slits and cavities. For high appearance, use dry cloth to sweep away and absorb excess mixture.*
4. *1kg of Core-Flooring mixture can apply on smooth flat surface with approximately 5 sq-m area.*
5. *Do not apply twice on same area to avoid damage of the preceding work.*



## 灰 金 剛

### 高級抗壓保護地台漆

灰金剛高級抗壓保護地台漆有別於其他地台漆，是高新技術產品，其特強的黏固力、抗壓力、抗磨力、耐酸、耐鹼、耐熱，可在潮濕的環境下施工等特點，是極為重要及理想的地台漆。

產品特性：

- 快速固化。
- 不開裂、不剝落。
- 出色的黏固力、抗壓力、抗磨力。
- 極優的抗酸、鹼化學品能力。
- 簡單而方便的施工方式。

適用範圍：

- 混凝土地面無縫地板
- 化學工業地面防腐蝕塗層

使用比例： A : B = 1:2 ( 重量計 )

使用方法： A : B 料混合後充份攪拌，然後以括板方式施工。

初固時間： 30 分鐘